




Rubber Duck Antenna



PARAMETER	Frequency Range (MHz)	Gain (dBi)	VSWR	Polarization	Power Handaling (Watt)	HPBW- Horizontal	Inpedance (Ohms)	Connector	Dimention (mm)
Rubber Duck Antenna									
TW3G/RUB/2dBi/01	824-960 & 1710-2170	2	≤ 1.2:1	Vertical	50	360°	50	N female	190
TW3G/RUB/4dBi/01	824-960 & 1710-2170	4	≤ 1.2:1	Vertical	50	360°	50	N female	190
TW/900/RUB/2dBi	824-960	2	≤ 1.8:1	Vertical	50	360°	50	N female	190
TW/1800/RUB/2dBi	1710-2170	2	≤ 1.8:1	Vertical	50	360°	50	N female	190
TW/2.3/RUB/5dBi/001	2300-2400	5	≤ 1.5:1	Vertical	50	360°	50	N female	190



Cont @ us

Cont ct us

TWIN ENGINEERS
 195 G.I.D.C Estate, Behind V.C.C.I. Complex,
 Makarpura, Vadodara, Gujarat-390010, INDIA
 PH: +91 265 2647987 / 9879105309
 Telefax: +91 265 2633894
 E-mail: info@twinantennas.com / sales@twinantennas.com
 Web: www.twinantennas.com
www.twin-antennas.com
www.twin-engineers.com