



# OMNI Antenna



2.4/14dBi

PARAMETER	Frequency Range ( MHz )	Gain ( dBi )	VSWR	Polarization	Power Handaling ( Watt )	HPBW-Vertical	HPBW-Horizantal	Inpedance ( Ohms )	Connector	Dimention ( mm )
<b>2.4 GHz OMNI Antenna ( Outdoor )</b>										
TW/2.4/OMNI/8dBi	2400 to 2500	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	600
TW/2.4/OMNI/12dBi	2400 to 2500	12	≤ 1.5:1	Linear , vertical	100	9°	360°	50	N female	1200
TW/2.4/OMNI/16dBi	2400 to 2500	16	≤ 1.5:1	Linear , vertical	100	6°	360°	50	N female	2000
<b>2.4 GHz OMNI Antenna ( Indoor )</b>										
TW/2.4/OMNI/6dBi	2400 to 2500	6	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/2.4/OMNI/8dBi	2400 to 2500	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
<b>3.3 GHz OMNI Antenna ( Outdoor )</b>										
TW/3.3/OMNI/8dBi	3300 to 3400	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	600
TW/3.3/OMNI/12dBi	3300 to 3400	12	≤ 1.5:1	Linear , vertical	100	9°	360°	50	N female	1200
TW/3.3/OMNI/16dBi	3300 to 3400	16	≤ 1.5:1	Linear , vertical	100	6°	360°	50	N female	2000
<b>3.3 GHz OMNI Antenna ( Indoor )</b>										
TW/3.3/OMNI/6dBi	3300 to 3400	6	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/3.3/OMNI/8dBi	3300 to 3400	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
<b>5.8 GHz OMNI Antenna ( Outdoor )</b>										
TW/5.8/OMNI/8dBi	5725 to 5875	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/5.8/OMNI/12dBi	5725 to 5875	12	≤ 1.5:1	Linear , vertical	100	9°	360°	50	N female	704
<b>5.8 GHz OMNI Antenna ( Indoor )</b>										
TW/5.8/Whip/6dBi	5725 to 5875	6	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/5.8/OMNI/8dBi	5725 to 5875	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550

<b>GSM OMNI Antenna</b>										
TW/900/OMNI/8dBi	824 to 960	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/900/OMNI/10dBi	824 to 960	10	≤ 1.5:1	Linear , vertical	100	9°	360°	50	N female	700
TW/400/OMNI/6dB	806 to 869	6dB	1.5:1	vertical	100	11°	360°	50	7/16 DIN Female	2700
TW/800/OMNI/10dB	806 to 869	10dB	1.4:1	vertical	100	9°	360°	50	7/16 DIN Female	4420
TW/800/OMNI/12dB	806 to 869	12dB	1.1:1	vertical	100	7°	360°	50	7/16 DIN Female	7416
<b>CDMA OMNI Antenna</b>										
TW/824/OMNI/8dBi	824 to 894	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/824/OMNI/10dBi	824 to 894	10	≤ 1.5:1	Linear , vertical	100	9°	360°	50	N female	700
<b>GSM 1800 OMNI Antenna</b>										
TW/1800/OMNI/8dBi	1710 to 2170	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	550
TW/1800/OMNI/12dBi	1710 to 2170	12	≤ 1.5:1	Linear , vertical	100	9°	360°	50	N female	550
<b>2.3GHz OMNI Antenna</b>										
TW/2.3/OMNI/8dBi	2300 To 2400	8	≤ 1.5:1	Linear , vertical	100	11°	360°	50	N female	600

	<p><b>TWIN ENGINEERS</b>  195 G.I.D.C Estate, Behind V.C.C.I. Complex,  Makarpura, Vadodara, Gujarat-390010, INDIA  PH: +91 265 2647987 / 9879105309  Telefax: +91 265 2633894  E-mail: info@twinantennas.com / sales@twinantennas.com  Web: www.twinantennas.com  www.twin-antennas.com  www.twin-engineers.com</p>
---	--