



<-- Gate Antenna

RFID Antenna

(Only antenna in India with Three Orientation Tag Reading)

PARAMETER	Frequency Range (MHz)	Read Renge	VSWR	Polarization	Tag Reading	Power Handaling (Watt)	HPBW- Horizontal	Inpedance (Ohms)	Connector	Dimention (mm)
RFID Antenna										
TW/13.56/RFID/PAD/01	13.56	25 cm	≤ 1.5:1	Circular	3D	10	N/A	50	SMA Male	250 X 250 X 30
TRFID/13.56/WT	13.56	1.2 Mtr	≤ 1.5:1	Circular	3D	10	N/A	50	SMA Male	2050 X 550 X 70
TW/RFID/UHF/CP/PANEL/01	860-870	3 Mtr	≤ 1.2:1	Circular	3D	10	N/A	50	SMA Male	250 X 250 X 30
TW/RFID/UHF/PANEL/7dBi	433	5 Mtr	≤ 1.5:1	Circular	3D	10	N/A	50	SMA Male	500 X 500 X 30
TW/402/RFID/RD/2.2dBi	402	15 cm	≤ 1.5:1	Vertical	20	10	360°	50	SMA Male	200 X 12 Dia
TW/433/RFID/RD/2.2dBi	433	15 cm	≤ 1.5:1	Vertical	20	10	360°	50	SMA Male	200 X 12 Dia
TW/866/RFID/RD/2.2dBi	866	15 cm	≤ 1.5:1	Vertical	20	10	360°	50	SMA Male	200 X 12 Dia



Cont ct us
Cont ct us

TWIN ENGINEERS
 195 G.I.D.C Estate, Behind V.C.C.I. Complex,
 Makarpura, Vadodara, Gujarat-390010, INDIA
 PH: +91 265 2647987 / 9879105309
 Telefax: +91 265 2633894
 E-mail: info@twinantennas.com / sales@twinantennas.com
 Web: www.twinantennas.com
 www.twin-antennas.com
 www.twin-engineers.com