

# Sector Antenna



2.4/16dBi



PARAMETER	Frequency Range ( MHz )	Gain ( dBi )	VSWR	Polarization	F/B Ratio ( dB )	Power Handaling	HPBW-Vertical	HPBW-Horizontal	Inpedance ( Ohms )	Connector	Dimention ( mm )
<b>2.4 GHz Vertical Sector Antenna</b>											
TW2.4/V SEC/12dBi/120°	2400 to 2500	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	120°	50	N female	600 X150 X50
TW2.4/V SEC/12dBi/90°	2400 to 2500	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	90°	50	N female	600 X150 X50
TW2.4/V SEC/12dBi/60°	2400 to 2500	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	60°	50	N female	400 X150 X50
TW2.4/V SEC/12dBi/45°	2400 to 2500	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	45°	50	N female	400 X150 X50
TW2.4/V SEC/14dBi/120°	2400 to 2500	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	120°	50	N female	600 X150 X50
TW2.4/V SEC/14dBi/90°	2400 to 2500	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	90°	50	N female	600 X150 X50
TW2.4/V SEC/14dBi/60°	2400 to 2500	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	60°	50	N female	600 X150 X50
TW2.4/V SEC/14dBi/45°	2400 to 2500	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	45°	50	N female	600 X150 X50
TW2.4/V SEC/16dBi/120°	2400 to 2500	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	120°	50	N female	950 X150 X50
TW2.4/V SEC/16dBi/90°	2400 to 2500	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	950 X150 X50
TW2.4/V SEC/16dBi/60°	2400 to 2500	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	60°	50	N female	950 X150 X50
TW2.4/V SEC/16dBi/45°	2400 to 2500	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	45°	50	N female	950 X150 X50
TW2.4/V SEC/17dBi/120°	2400 to 2500	17	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	120°	50	N female	950 X150 X50
TW2.4/V SEC/17dBi/90°	2400 to 2500	17	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	950 X150 X50
TW2.4/V SEC/17dBi/60°	2400 to 2500	17	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	60°	50	N female	950 X150 X50
TW2.4/V SEC/17dBi/45°	2400 to 2500	17	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	45°	50	N female	950 X150 X50
<b>Special Sector Antenna</b>											
TW2.4/Xpol SEC/13dBi/90°	2400 to 2500	13	≤ 1.5:1	± 45 deg(cross)	28	200Watt(CW)	18°	90°	50	N female	600 X150 X50
TW2.4/Xpol SEC/16dBi/90°	2400 to 2500	16	≤ 1.5:1	± 45 deg(cross)	28	200Watt(CW)	15°	90°	50	N female	900 X150 X50
TW2.4/V SEC/12dBi-90°/45°	2400 to 2500	12	≤ 1.5:1	Vertical / horizontal	28	200Watt(CW)	45°	90°	50	N female	400 X110x 60
TW2.4/V SEC/12dBi-120°/45°	2400 to 2500	12	≤ 1.5:1	Vertical / horizontal	28	200Watt(CW)	45°	120°	50	N female	250 X210x 70
<b>2.4GHz Horizontal Sector Antenna</b>											
TW2.4/H SEC/14dBi/120°	2400 to 2500	14	≤ 1.5:1	Horizontal	28	200Watt(CW)	12	120°	50	N female	900X100X65
TW2.4/H SEC/16dBi/120°	2400 to 2500	16	≤ 1.5:1	Horizontal	28	200Watt(CW)	9	120°	50	N female	1120X100X65
TW2.4/H SEC/18dBi/120°	2400 to 2500	18	≤ 1.5:1	Horizontal	28	200Watt(CW)	6	120°	50	N female	1450x104x54
<b>5.8 GHz Vertical Sector Antenna</b>											
TW5.8/V SEC/12dBi/120°	5725 to 5875	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	120°	50	N female	400 X150 X50
TW5.8/V SEC/12dBi/90°	5725 to 5875	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	90°	50	N female	400 X150 X50
TW5.8/V SEC/12dBi/60°	5725 to 5875	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	60°	50	N female	400 X150 X50
TW5.8/V SEC/12dBi/45°	5725 to 5875	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	45°	50	N female	400 X150 X50
TW5.8/V SEC/14dBi/120°	5725 to 5875	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	120°	50	N female	600 X150 X50
TW5.8/V SEC/14dBi/90°	5725 to 5875	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	90°	50	N female	600 X150 X50
TW5.8/V SEC/14dBi/60°	5725 to 5875	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	60°	50	N female	600 X150 X50
TW5.8/V SEC/14dBi/45°	5725 to 5875	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	45°	50	N female	600 X150 X50

<b>2.3/2.4/2.5/2.7 GHz Vertical Sector Antenna</b>												
TW2.3/V SEC/12dBi/120°	2300 to 2400	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	120°	50	N female	600 X150 X50	
TW2.3/V SEC/12dBi/90°	2300 to 2400	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	90°	50	N female	600 X150 X50	
TW2.3/V SEC/12dBi/60°	2300 to 2400	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	60°	50	N female	400 X150 X50	
TW2.3/V SEC/12dBi/45°	2300 to 2400	12	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	45°	50	N female	400 X150 X50	
TW2.3/V SEC/14dBi/120°	2300 to 2400	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	120°	50	N female	600 X150 X50	
TW2.3/V SEC/14dBi/90°	2300 to 2400	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	90°	50	N female	600 X150 X50	
TW2.3/V SEC/14dBi/60°	2300 to 2400	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	60°	50	N female	600 X150 X50	
TW2.3/V SEC/14dBi/45°	2300 to 2400	14	≤ 1.5:1	Vertical	28	200Watt(CW)	11°	45°	50	N female	600 X150 X50	
TW2.3/V SEC/16dBi/120°	2300 to 2400	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	120°	50	N female	950 X150 X50	
TW2.3/V SEC/16dBi/90°	2300 to 2400	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	950 X150 X50	
TW2.3/V SEC/16dBi/60°	2300 to 2400	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	60°	50	N female	950 X150 X50	
TW2.3/V SEC/16dBi/45°	2300 to 2400	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	45°	50	N female	950 X150 X50	
TW2.3/V SEC/18dBi/120°	2300 to 2400	18	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	120°	50	N female	950 X150 X50	
TW2.3/V SEC/18dBi/90°	2300 to 2400	18	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	950 X150 X50	
TW2.3/V SEC/18dBi/60°	2300 to 2400	18	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	60°	50	N female	950 X150 X50	
TW2.3/V SEC/18dBi/45°	2300 to 2400	18	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	45°	50	N female	950 X150 X50	
TW2.3/V SEC(M)/16dBi/90°	2300 to 2400	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	600 X150 X50	
TW2.4/V SEC(M)/16dBi/90°	2400 to 2500	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	600 X150 X50	
TW2.5/V SEC(M)/16dBi/90°	2500 to 2700	16	≤ 1.5:1	Vertical	28	200Watt(CW)	9°	90°	50	N female	600 X150 X50	
<b>Wi-Max Cross Polar Sector Antenna</b>												
TW2.3/Xpol SEC/18dBi/90°	2300 to 2700	18	≤ 1.5:1	Vertical	28	200Watt(CW)	6.5°	90°	50	N female	1260 X120 X50	
TW2.3/Xpol SEC/18dBi/65°	2300 to 2700	18	≤ 1.5:1	Vertical	28	200Watt(CW)	6.5°	65°	50	N female	1260 X120 X50	
TW3.3/Xpol SEC/18dBi/90°	3300 to 3500	18	≤ 1.5:1	Vertical	28	200Watt(CW)	6.5°	90°	50	N female	1260 X120 X50	
TW3.3/Xpol SEC/18dBi/65°	3300 to 3500	18	≤ 1.5:1	Vertical	28	200Watt(CW)	6.5°	65°	50	N female	1260 X120 X50	



**TWIN ENGINEERS**

195 G.I.D.C Estate, Behind V.C.C.I. Complex,  
Makarapura, Vadodara, Gujarat-390010, INDIA  
PH: +91 265 2647987 / 9879105309

Telefax: +91 265 2633894

E-mail: [info@twinantennas.com](mailto:info@twinantennas.com) / [sales@twinantennas.com](mailto:sales@twinantennas.com)

Web: [www.twinantennas.com](http://www.twinantennas.com)

[www.twin-antennas.com](http://www.twin-antennas.com)

[www.twin-engineers.com](http://www.twin-engineers.com)